

Louisville Metro Air Pollution Control District
PM_{2.5} Monitoring Report
July 2020

This report summarizes PM_{2.5} data collected by Federal Reference Method (FRM) and Federal Equivalent Method (FEM) instruments. Measurements are reported as 24-hour averages in micro-grams per cubic meter (µg/m³). The data are subject to further quality assurance checks and are not final.

PM_{2.5} Monthly Data Summary for June 2020

Site Name	Maximum		Minimum		Sample	Monthly
	Conc.	Date	Conc.	Date	Recovery	Average
Algonquin Parkway *	22.8	6/27/20	4.2	6/11/20	NA	9.8
Durrett Lane	21.6	6/27/20	4.5	6/11/20	NA	9.6
Cannons Lane	22.0	6/27/20	4.6	6/1/20	NA	9.6
Watson Lane	21.3	6/27/20	5.3	6/11/20	NA	9.7
Overall	22.8	6/27/20	4.2	6/11/20	NA	9.7

* LMAPCD officially changed the Firearms Training site name to Algonquin Parkway


PM_{2.5} Monthly Averages Tracking Table for 2010-2020

Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Months >Annual Standard
2010	13.3	16.3	12.2	12.2	11.0	14.1	16.0	16.4	11.0	17.0	12.6	13.7	4
2011	15.2	10.6	9.7	8.6	12.1	14.1	19.7	16.2	11.5	9.0	7.6	9.9	3
2012	8.9	9.5	9.2	7.2	11.7	10.9	12.5	11.9	8.6	7.3	13.1	9.6	0
2013*	10.5	10.0	8.5	7.6	8.8	11.6	10.1	12.7	11.9	9.3	7.2	10.7	0
2014	7.5	14.3	11.7	9.6	10.7	14.0	16.4	13.6	9.9	7.9	9.8	12.4	5
2015	10.9	11.0	11.3	6.9	10.2	10.1	13.1	10.0	9.7	7.5	8.5	7.7	1
2016	8.9	9.5	6.4	7.1	7.1	8.5	7.4	8.9	9.3	8.1	11.3	9.3	0
2017	7.7	8.1	6.6	5.8	7.2	6.7	11.3	9.3	8.5	6.8	10.5	10.7	0
2018	9.7	9.6	8.4	6.5	11.0	10.4	11.9	11.7	7.2	7.1	12.9	11.0	1
2019 **	11.0	11.0	11.1	8.2	9.6	8.2	10.6	8.8	10.4	8.2	11.4	12.0	0
2020 **	9.4	9.3	8.8	9.3	6.8	9.7							0
Average	10.3	10.8	9.4	8.1	10.3	10.8	12.9	12.0	9.8	8.8	10.5	10.7	

*The new PM_{2.5} standard of 12 µg/m³ became effective on March 18, 2013

** Data from continuous FEM Instruments

PM_{2.5} Monthly Averages 5-Year Trend



National Ambient Air Quality Standards (NAAQS):

National Ambient Air Quality Standards consist of primary and secondary standards. The primary standards define levels of air quality which EPA judges are necessary, with an adequate margin of safety, to protect the public health. The secondary standards define levels of air quality which EPA judges necessary to protect the public welfare from any known or anticipated adverse effects of a pollutant. For PM_{2.5} the levels of the primary and secondary standards are the same.

National Ambient Air Quality Standard for PM_{2.5} - Annual Standard:

The annual standard is designed to provide an appropriate level of protection from long-term exposure to PM_{2.5}. The standard is met when the annual design value is less than or equal to 12 µg/m³. The standard changed from 15 µg/m³ to 12 µg/m³ on March 18, 2013. The annual design value is calculated by averaging the annual means of 3 consecutive complete years of air quality data. The table below compares data collected from 2014 through year-to-date 2020 to the PM_{2.5} annual standard.

PM_{2.5} Annual Means and Annual Design Values

Site Name	Annual Means µg/m ³							Annual Design Values				
	2014	2015	2016	2017	2018	2019	2020	2014-2016	2015-2017	2016-2018	2017-2019	2018-2020
Algonquin*	11.2	10.4	8.3	8.3	9.5	10.2	8.8	10.0	9.0	8.7	9.3	9.5
Durrett Lane	12.0	10.0	9.2	8.9	10.2	10.4	9.0	10.4	9.4	9.4	9.8	9.8
Cannons Lane	11.0	9.5	7.9	7.9	9.1	9.6	8.6	9.5	8.4	8.3	8.8	9.1
Watson Lane	12.2	10.4	8.4	8.1	10.5	10.0	9.2	10.3	9.0	9.0	9.6	9.9

Bold: Design value for Louisville

* Site name changed from Firearms Training to Algonquin Parkway

National Ambient Air Quality Standard for PM_{2.5} - 24-Hour (Daily) Standard:

The 24-hour standard is designed to provide an appropriate level of protection from short-term exposure to PM_{2.5}. The standard is met when the 24-hour design value is less than or equal to 35 µg/m³. The design value is based on 3 consecutive complete years of air quality data and is calculated by taking the average of the 98th percentile value for each of the 3 years. The 98th percentile value is the 24-hour average out of a year of PM_{2.5} monitoring data below which 98 percent of all 24-hour averages fall. The table below compares data collected from 2014 through year-to-date 2020 to the 24-hour standard for PM_{2.5}.

PM_{2.5} Annual 98th Percentiles and 24-Hour Design Values

Site Name	Annual 98 th Percentile Value µg/m ³							24-Hour Design Values				
	2014	2015	2016	2017	2018	2019	2020	2014-2016	2015-2017	2016-2018	2017-2019	2018-2020
Algonquin*	24.3	22.3	17.0	17.8	23.0	20.2	17.2	21.2	19.0	19.3	20.3	20.1
Durrett Lane	26.0	22.1	18.7	20.7	24.7	22.9	16.2	22.3	20.5	21.4	22.8	21.3
Cannons Lane	23.9	21.7	18.7	17.2	22.2	20.5	15.2	21.4	19.2	19.4	20.0	19.3
Watson Lane	26.2	22.8	16.2	17.7	24.3	21.4	17.7	21.7	18.9	19.4	21.1	21.1

Bold: Design value for Louisville

* Site name changed from Firearms Training to Algonquin Parkway

Louisville Metro Air Pollution Control District


Special Report for June 27th Saharan Dust PM Event

This Special Report shows PM_{2.5} data for a period of time when the Louisville Metropolitan area was impacted by long range transport of Saharan Dust from Africa.

Date	Cannons Lane	Firearms Training	Carrithers	Watson Lane	Durrett Lane
	24 hr avg (ug/m3)	24 hr avg (ug/m3)	24 hr avg (ug/m3)	24 hr avg (ug/m3)	24 hr avg (ug/m3)
06/26/20	11.0	11.5	10.3	10.3	11.0
06/27/20	22.0	22.7	20.6	21.3	21.5

*see below for an explanation of filter based FRM versus continuous FEM monitors

The NAAQS is a health based standard. The negative health effects of PM_{2.5} are regulated based on 24-hour averages (35 µg/m³) and annual averages (12 µg/m³). The peak hourly concentrations occurred during the late morning hours on June 27th. PM_{2.5} concentrations sharply declined later that evening when the Louisville area was impacted by thunderstorms.



*A **filter based FRM (Federal Reference Method) monitor** pulls ambient air through a filter for 24 hours at a constant flow rate. The filter is weighed before and after the sampling and the concentration is calculated using the mass accumulated on the filter and the volume of air sampled. LMAPCD is using a contract lab to weigh the filters. There is typically a three week lag time between data collection and results. LMAPCD currently operates two filter-based PM_{2.5} FRM monitors. The data presented in this report show data collected from **continuous FEM (Federal Equivalent Method) monitors**. The hourly FEM data are used to update the Air Quality Index (alerts) and allows LMAPCD to evaluate spikes on a higher resolution than the traditional FRM 24-hour average filter method. LMAPCD currently operates five PM_{2.5} continuous FEM monitors and two PM₁₀ FEM continuous monitors.

Louisville Metro Air Pollution Control District


Special Report for PM_{2.5} July 4-5, 2020

This Special Report shows the 24-hour PM_{2.5} averages for July 4th and July 5th. A 24-hour average above 35 µg/m³ exceeds the NAAQS.

Date	Cannons Lane	Firearms Training	Carrithers	Watson Lane	Durrett Lane
	24 hr avg (ug/m3)	24 hr avg (ug/m3)	24 hr avg (ug/m3)	24 hr avg (ug/m3)	24 hr avg (ug/m3)
07/04/20	23.6	20.5	28.2	28.4	36.2
07/05/20	25.5	26.9	22.3	29.3	34.2

*see below for an explanation of filter based FRM versus continuous FEM monitors

The NAAQS is a health based standard. The negative health effects of PM_{2.5} are regulated based on 24-hour averages (35 µg/m³) and annual averages (12 µg/m³). The hourly spikes during July 4th are shown below. Durrett Lane had the highest one-hour average of 290.7 µg/m³. PM_{2.5} concentrations slowly declined during the early morning hours of July 5th.



*A **filter based FRM (Federal Reference Method) monitor** pulls ambient air through a filter for 24 hours at a constant flow rate. The filter is weighed before and after the sampling and the concentration is calculated using the mass accumulated on the filter and the volume of air sampled. LMAPCD is using a contract lab to weigh the filters. There is typically a three week lag time between data collection and results. LMAPCD currently operates two filter-based PM_{2.5} FRM monitors. The data presented in this report show data collected from **continuous FEM (Federal Equivalent Method) monitors**. The hourly FEM data are used to update the Air Quality Index (alerts) and allows LMAPCD to evaluate spikes on a higher resolution than the traditional FRM 24-hour average filter method. LMAPCD currently operates five PM_{2.5} continuous FEM monitors and two PM₁₀ FEM continuous monitors.

Louisville Metro Air Pollution Control District
8-Hour Ozone Monitoring Report
July 2020

This report summarizes ozone data collected by Automated Equivalent Method (AEM) ozone analyzers located within the Louisville Metropolitan Statistical Area. Measurements are reported as 8-hour averages in parts-per-billion (ppb). The data are subject to further quality assurance checks and are not final.

2020 8-Hour Ozone Maximum Values and Exceedances through July 7th

Date	# of 8-Hour Exceeds	# of Days Exceeds	Charlestown Clark County IN	New Albany Floyd County IN	Carrithers Jefferson County KY	Watson Lane Jefferson County KY	Cannons Lane Jefferson County KY	Buckner Oldham County KY	Shepherdsville Bullitt County KY
03/01/20	0	0	51.6	51.0	55.3	50.1	53.8	53.6	54.5
04/03/20	0	0	57.1	52.8	56.3	55.7	57.0	55.7	54.0
04/04/20	0	0	56.7	52.3	57.5	50.8	56.2	59.7	53.8
05/02/20	0	0	54.3	54.3	53.3	50.3	55.5	56.7	53.5
05/04/20	0	0	52.0	51.7	55.3	58.7	54.5	51.7	56.2
06/06/20	0	0	65.6	60.1	68.1	57.3	65.6	57.8	60.6
06/13/20	0	0	68.6	62.3	68.1	64.0	68.6	60.8	65.2
06/17/20	2	1	66.5	66.3	68.7	71.8	71.5	69.7	65.6
06/19/20	0	0	62.1	62.8	69.0	64.6	68.3	66.1	66.2
06/20/20	0	0	63.7	62.7	69.8	57.0	67.8	66.1	61.5
07/06/20	1	1		66.5	54.6	57.1	75.7	46.8	49.2
07/07/20	2	1		83.6	54.2	54.3	72.0	50.1	47.8
Total Exceeds	5	3	0	1	0	1	3	0	0
Truncated 4th Maximum				62	68	58	68	60	61

Values in **BOLD/RED** exceed the level of the 2015 ozone standard of 70 ppb (parts-per-billion). This standard applies to air monitoring data beginning with the 2016 ozone season.

NA - Indicates data were not available.

8-Hour Ozone Exceedances:

The National Ambient Air Quality Standard for ozone is measured as an 8-hour average. An ozone exceedance occurs when the highest 8-hour average for each day is greater than the NAAQS. The NAAQS was lowered from 80 ppb to 75 ppb in 2007 and from 75 ppb to 70 ppb in 2016. The data below lists the number of exceedances based on the NAAQS at the time the data was collected.


2007-2020 8-Hour Ozone Exceedance Summary through July 7th

Year	Charles-town	New Albany	Bates & Carri-thers	Watson	WLKY& Cannons Lane	Buckner	Shepherds-ville	Louisville MSA Total		Jefferson County Total	
								Exceedances	Days	Exceedances	Days
2007	8	3	8	4	2	3	0	28	16	14	11
2008	3	3	2	2	1	4	2	17	9	5	5
2009	0	0	2	4	0	0	0	6	5	6	5
2010	4	2	3	3	15	8	2	37	19	21	15
2011	6	5	6	5	8	13	1	44	23	19	14
2012	8	13	7	11	13	14	4	70	23	31	17
2013	0	0	0	0	0	0	0	0	0	0	0
2014	1	2	0	2	2	0	0	7	3	4	3
2015	3	0	4	1	4	2	0	14	6	9	5
2016	7	6	5	3	14	3	1	39	19	22	16
2017	1	5	1	1	4	1	0	13	6	6	4
2018	4	5	3	2	6	1	2	23	11	11	8
2019	1	0	2	0	2	1	0	6	4	4	2
2020	0	1	0	1	3	0	0	5	3	4	3

* Cannons Lane replaced WLKY in 2010. Data through 2009 are from WLKY.

* Carrithers replaced Bates in 2018. Data through 2017 are from Bates.

Historical Graph of 8-Hour Ozone Exceedances



National Ambient Air Quality Standard for Ozone - 8-Hour Standard:


Attainment of the 8-hour standard for ozone at an individual monitor is achieved when the three-year average of the annual fourth-highest daily maximum (4th maximum) 8-hour average ozone concentration is less than 71 ppb. This three-year average is the design value for that monitor. The Louisville MSA row represents the largest 4th maximum and design value* for all monitors within the MSA.

8-Hour Ozone 4th Maximums and Design Values through July 7th

Site Name	4 th Maximums							8-Hour Design Values				
	2014	2015	2016	2017	2018	2019	2020	2014-2016	2015-2017	2016-2018	2017-2019	2018-2020
Charlestown	66	74	73	68	71	64		71	71	70	67	
New Albany	66	67	73	74	73	63	62	68	71	73	70	66
Bates/Carrithers	65	71	73	65	70	64	68	69	69	69	66	67
Watson Lane	69	69	70	66	69	65	58	69	68	68	66	64
Cannons Lane	68	76	76	72	77	68	68	73	74	75	72	71
Buckner	68	73	69	64	69	65	60	70	68	67	66	65
Shepherdsville	65	67	67	63	68	60	61	66	65	66	63	63
Louisville MSA	69	76	76	74	77	68	68	73	74	75	72	71

* Design Value calculations are approximations based on preliminary summary data and may differ from official design value calculations

8-Hour Ozone Design Value Trend Chart



**Louisville Metro Air Pollution Control District
Air Monitoring Report for Sulfur Dioxide (SO₂)
July 2020**

On June 2, 2010, EPA strengthened the primary National Ambient Air Quality Standard for SO₂. Specifically, EPA replaced the existing annual (30 ppb) and 24-hour (140 ppb) primary standards with a new 1-hour standard set at 75 ppb. The 1-hour standard was set to better protect public health by reducing exposure to high short-term concentrations of SO₂. The new standard took effect August 23, 2010.

Exceedances of the 1-Hour SO₂ Standard:

An exceedance occurs when a measured 1-hour average is greater than 75 ppb. Since up to twenty-four 1-hour averages are recorded each day, multiple exceedances may occur in one day. However, only the maximum 1-hour average (Daily Max) for each day is used in determining if the area is in compliance with the standard. The table below indicates the number of exceedances and the daily maximums reported thus far this year. The data are subject to further quality assurance checks and are not final.

SO₂ Daily Maximums and Exceedances through June 30th

Date	Algonquin Parkway		Watson Lane Elementary		Cannons Lane NCore		New Albany Indiana	
	Exceeds	Daily Max	Exceeds	Daily Max	Exceeds	Daily Max	Exceeds	Daily Max
01/07/20		4.4		3.0		1.5		1.4
01/09/20		2.1		5.4		0.1		2.6
01/30/20		1.8		2.1		2.3		1.2
02/02/20		5.0		3.1		2.3		1.1
02/03/20		1.7		6.8		4.7		1.5
02/21/20		1.2		8.5		1.2		1.6
02/22/20		2.2		6.7		4.0		2.7
03/05/20		3.2		6.7		0.7		NA
03/09/20		4.6		5.1		0.1		3.3
03/17/20		0.2		1.1		9.1		1.6
04/11/20		1.3		1.1		5.9		2.1
04/22/20		1.6		1.7		2.9		3.5
04/29/20		3.5		5.9		2.5		2.7
05/07/20		3.9		0.9		1.2		1.4
05/16/20		1.0		13.7		0.7		1.2
05/28/20		0.9		1.1		6.3		1.3
06/02/20		2.6		4.9		18.6		2.4
06/20/20		2.3		8.4		6.9		2.1
06/30/20		4.1		1.5		1.4		2.8
Totals/Max	0	5.0	0	13.7	0	18.6	0	3.5
99 th Percentile		4.6		8.5		9.1		3.3

NA - Indicates data were not available

Attainment of the SO₂ Standard:

Attainment of the new standard is achieved when the 3-year average of the 99th percentile annual distribution of the daily maxima is less than or equal to 75 ppb. Since this value can be calculated from historical data, the chart below indicates those values based on 2014-2020 data.

SO₂ Annual 99th Percentiles and Annual Design Values

Site Name	Annual 99 th Percentiles (ppb)							Annual Design Values				
	2014	2015	2016	2017	2018	2019	2020	2014-2016	2015-2017	2016-2018	2017-2019	2018-2020
Watson Lane	149	54	26	14	16	15	9	76	31	19	15	13
Algonquin	42	25	16	11	12	6	5	28	17	13	10	8
Cannons Lane	29	19	8	7	8	9	9	19	11	8	8	9
New Albany	44	26	11	8	9	7	3	27	15	9	8	7

* Design Value calculations are approximations based on preliminary summary data and may differ from official design value calculations